

SP&NSPLIT TYPE DISTRIBUTION BOARDS (DIN RAIL BOARDS)

IP 41

SP&N

IP41 SPLIT LOAD WITH INCOMERS

SPN split Din Rail Distribution boards are available in various designations and can be customized as required. Our Basic colours are White & Grey, optional colours can be provided as per required







ITEM	Busbar Rating	SPN Split	Incomer Isolator	Lighting ELCB 300mA	Power ELCB 30mA	Width	Height mm	Depth
1	150A	2+2W	100A	63A	63A	320	355	85
2	150A	4+2W	100A	63A	63A	320	355	85
3	150A	4+4W	100A	63A	63A	3.20	355	85
4	150A	6+2W	100A	63A	63A	320	355	85
5	150A	6+4W	100A	63A	63A	320	355	85
6	150A	6+6W	100A	63A	63A	320	355	85
7	150A	8+2W	100A	63A	63A	320	355	85
8	150A	8+4W	100A	63A	63A	320	355	85

0	150A	8+oW	100A	63A	63A	320	420	85
10	150A	8+8W	100A	63A	63A	320	420	85
11	150A	10+2W	100A	63A	63A	320	420	85
12	150A	10+4W	100A	63A	63A	320	420	85
13	150A	10+6W	100A	63A	63A	320	420	85
14	150A	12+2W	100A	63A	63A	320	420	85
15	150A	12+4W	100A	63A	63A	320	420	8.5
16	150A	12+6W	100A	63A	63A	320	420	8.5
17	150A	12+8W	100A	63A	63A	320	420	85

BSLI MCB Distribution Board arranged with:

- Single phase 240V 50Hz AC Supply
- MCB's are SP,DP
- Power and Lighting Section splited by separate ELCB and Interior
- · Interior with Copper timed coated busbar
- · Busbar rated for 150 amps
- · Surface or Flush mounted
- Ambient temperature 50°C
 Cabling and Installation
- · Comprehensive cable entry facilities
- · Ease of Installation, cabling & maintenance
- · Universal fixing facilities
- Earth and neutral bars are mounted on a separate interior
- Sufficient space for cable/wires
 Various brands & Rating of Isolators, ELCB's,
 MCB's can be provided as per our stock
 availability, IP 65 can be manufactured as required