

IP 41

NON SPLIT TYPE DISTRIBUTION BOARDS (PLUG IN TYPE)

TP&N

TPN non split Plug in type

Distribution boards are

available in various designations and can be customized as required. Our Basic colours are White & Grey, optional colours can be provided as required.

BSLI MCB Distribution Board arranged with:

- . Three phase 415V 50Hz AC Supply.
- · MCB's are SP,DP & TP.
- Power or Lighting Section with ELCB or Isolator & ELCB+Isolator.
- · Interior with Copper tinned coated busbar.
- Busbar rated for 150 amps.
- · Surface or Flush mounted.
- Ambient temperature 50 °C.

Cabling and Installation:

- · Comprehensive cable entry facilities,
- · Ease of Installation, cabling & maintenance.
- Universal fixing facilities.
- · Neutral bars are mounted on a separate insulator.
- · Sufficient space for cable/wires.

Various brands & Rating of Isolators, ELCB's, MCB's can be provided as per our stock availability. IP 65 can be manufactured as required.



			н		
00	0	00	0	D	
-	w		_		

ITEM	Busbar Rating	TPN Non Split	Incomer Isolator	Incomer 300mA 30mA		Width	Height mm	Depth
1	150A	2W	100A	63A	63A	355	380	85
2	150A	4W	100A	63A	63A	355	460	85
3	150A	6W	100A	63A	63A	355	540	85
4	150A	8W	100A	63A	63A	355	610	85
5	150A	10W	100A	63A	63A	355	700	85
6	150A	12W	100A	63A	63A	355	760	85
7	150A	14W	100A	63A	63A	355	850	85